

### CA- INDUSTRIAL GRADE CIRCULATING FANS

Canarm LFI's CA circulating fans economically provide relief from summer heat by creating a gentle air movement. They effectively cool large areas in factories, stores, restaurants and other public places. These fans have a low RPM motor which allows them to operate quietly.

The Floor Pedestal type fans come with a sturdy base and are supported by an adjustable tubular steel post which provides maximum stability. The Wall Mount fans are anchored with a sturdy wall bracket. There is also an optional ceiling mount.

On all fan models, the fan assembly can be tilted on a swivel bracket to direct air stream upwards or downwards. Available with oscillating motor on the pedestal and wall models.

#### **FEATURES**

- · Rugged, high performance model.
- Available in 24" & 30" sizes.
- 1/4 HP, 3 speed, totally enclosed ball bearing motor with thermal overload protection.
- Fan motor RPM 1100/950/850.
- Available with oscillating motor on the pedestal and wall models.
- · Heavy gauge aluminum, well balanced fan blades.
- Air stream adjustable in all directions.
- · Complete with 10', 120V grounded cord set.
- Attractive powder coated front and rear guards, meet OSHA standards.





MODEL NUMBER	FAN SIZE	DESCRIPTION	СҒМ	VOLT	AMPS	SHIPPING WEIGHT (LBS)	
PEDESTAL FANS							
CA24P-C	24"	3 SPEED	7100/6300/5300	115	2.7	60	
CA24POSC-C	24	3 SPEED OSCILLATING	7100/6300/5300	115	2.7	60	
CA30P-C	30"	3 SPEED	8300/7300/6300	115	2.7	83	
CA30POSC-C	30	3 SPEED OSCILLATING	8300/7300/6300	115	2.7	83	
WALL MOUNTING FANS							
CA24W-C	24"	3 SPEED	7100/6300/5300	115	2.7	40	
CA24WOSC-C	24	3 SPEED OSCILLATING	7100/6300/5300	115	2.7	40	
CA30W-C	30"	3 SPEED	8300/7300/6300	115	2.7	50	
CA30WOSC-C	30	3 SPEED OSCILLATING	8300/7300/6300	115	2.7	50	
HEADS ONLY							
CA24-C	24"	3 SPEED	7100/6300/5300	115	2.7	40	
CA24OSC-C		3 SPEED OSCILLATING	7100/6300/5300	115	2.7	40	
CA30-C	30"	3 SPEED	8300/7300/6300	115	2.7	50	
CA30OSC-C	30	3 SPEED OSCILLATING	8300/7300/6300	115	2.7	50	

FAN HEAD MOUNTING ACCESSORIES SHOWN BELOW.

### **VELOCITY MAPPING CHARTS**

These charts indicate the air distribution patterns of the CA fans. They are a graphic illustration of air velocity in feet per minute.







# **MOUNTING ACCESSORIES**

	MODEL	DDEL DESCRIPTION	
1	CFKPB	KNOCK DOWN PEDESTAL BASE	36
	CFWB	WALL BRACKET	6
7	CFCM	CEILING MOUNT (NON OSCILLATING FANS ONLY)	9
1	DF36X36	DOCK ARM	-



**CFKPB** 



## PBKD /WMKD - COMMERCIAL **CIRCULATING FANS**

Canarm/LFI's high velocity commercial fans economically provide relief from summer heat by creating a gentle air movement. Pedestal type fans come with a sturdy base and adjustable pole. All fans have a 3 speed motor with industrial grade aluminum blades.

#### **FEATURES**

- · Commercial duty circulating fans (Knock Down).
- · Painted aluminum blades.
- · Standard OSHA guard.
- · Motors are thermally protected.
- Available in 24" and 30" stationary and oscillating models.
- Packaged in one box, complete with mounting accessories.

Complete with 10', 120V grounded plug.								
FAN SIZE	MODEL NUMBER & WEIGHT (LBS)				DESCRIPTION	H.P.	SUPPLY CFM	
	PEDESTAL FAN	WEIGHT (LBS)	WALL MOUNT FAN	WEIGHT (LBS)	DESCRIPTION		001121 01111	
24"	PBKD24-3SP	74	WMKD24-3SP	38	3 Speed	1/4	6600/5900/4900	
24"	PBKD24-OSC	78	WMKD24-OSC	42	3 Speed Oscillating	1/4	6600/5900/4900	
30"	PBKD30-3SP	80	WMKD30-3SP	46	3 Speed	1/4	8300/7300/6300	
30"	PBKD30-OSC	84	WMKD30-OSC	49	3 Speed Oscillating	1/4	8300/7300/6300	



### **CCU - COMMERCIAL CIRCULATING FANS**

Canarm/LFI's high velocity commercial fans economically provide relief from summer heat by creating a gentle air movement. Pedestal type fans come with a sturdy base and adjustable pole. All fans have a 3 speed motor with industrial grade aluminum blades.

### **FEATURES**

- · Commercial duty circulating fans (Knock Down).
- 20" stationary models.
- Adjustable pedestal (54"-64") or wall mount bracket.
- · 3 speeds.
- · Painted aluminum blades.
- · Standard OSHA guard.
- · Motors are thermally protected.
- · Complete with 10', 120V grounded plug.
- · 20" pedestal complete with wheel kit.

MODEL	FAN SIZE	DESCRIPTION	H.P.	SUPPLY CFM	WEIGHT (LBS)
CCUW20	20"	3 Speed Wall Fan	1/4	6200/5200/4200	26